

GV-1480A Combo Card



Especificaciones

Interfase		PCI-E
Tipo de entrada		DB15 x 2 (Video), DB9 x 2 (Audio)
Entradas de Video		16 Cams
Entradas de Audio		16 Channels
TV Output		RCA Connector x 1
Grabación	CIF	480 fps (NTSC), 400 fps (PAL)
	D1	240 fps (NTSC), 200 fps (PAL)
	Turbo VGA	416 fps (NTSC), 400 fps (PAL)
	Turbo D1	352 fps (NTSC), 320 fps (PAL)
Visualización	CIF	480 fps (NTSC), 400 fps (PAL)
	D1	480 fps (NTSC), 400 fps (PAL)
Video Resolución	NTSC	720x480, 720x480 De-interlace, 640x480, 640x480 De-interlace, 360x240, 320x240
	PAL	720x576, 720x576 De-interlace, 640x480, 640x480 De-interlace, 360x288, 320x240
Formato de Compresión		Geo MPEG4, Geo MPEG4 (ASP), Geo H264, Geo H264 V2
GV-Multi Quad Card Support		Si
GV-Loop Through Card Support		Si
GV-NET/IO Card Support		Si
Dimensiones (W x H)		187.7 x 117.1 (mm) / 7.38 x 4.61 (in)
Guía de instalación		Single Card Two Cards

Nota:

GV-1480 no es compatible con chipset VIA, ATI , y sistemas operativos Windows 64-bits.

Requerimientos mínimos para una placa		
OS	Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista (No soporta versiones de Windows 64-bits)	
CPU	Core 2 Duo-3.0 GHz	
RAM	Windows 2000 / XP: 2 x 512 MB Dual Channels Windows Vista / Server 2003: 2 x 1 GB Dual Channels	
HDD	250 GB	
VGA	ATI Radeon X1300 PCI-E / NVIDIA GeForce 7300 PCI-E	
DirectX	9.0c	
Requerimientos mínimos para dos placas		
OS	Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista (No soporta versiones de Windows 64-bits)	
CPU	Core 2 Quad, 2.4 GHz	
RAM	2 x 1 GB Dual Channels	
HDD	500 GB	
VGA	ATI Radeon X1300 PCI-E / NVIDIA GeForce 7300 PCI-E	
DirectX	9.0c	
Requerimientos mínimos para Turbo Mode		
Modelo	GV-1480A x 1	GV-1480A x 2
CPU	Core 2 Quad, 2.4 GHz	Core i7-920, 2.66 GHz
RAM	2 x 512 MB Dual Channels (Windows 2000 / XP) 2 x 1 GB Dual Channels (Windows Server 2003 / Vista)	2 x 1 GB Dual Channels
VGA	ATI Radeon X1300 PCI-E / NVIDIA n7300 PCI-E	ATI Radeon X1300 PCI-E / NVIDIA GeForce 7300 PCI-E
HDD	320 GB	750 GB

